

## PAC GS3 Range

## Readers—LF

### 909020116 – PAC LF Vandal Resistant Reader - black

The Vandal Resistant Reader is designed to work in the most demanding of operating environments as it provides a robust, intruder-graded access reader. The Vandal Resistant Reader is ideal for internal or external installations.



- Raised key symbol on the front with audible and visual user feedback for Equality Act compliance
- Comes with pre-connected 2m cable for ease of installation
- Supports the following ID Devices:
  - PAC
  - KeyPAC
  - Wiegand (many variants)
- Integral Tamper circuit and Mounting Plate
- Reader line tamper configurable when used in conjunction with PAC 512 controllers

<b>Part Number(s)</b>	909020116 – PAC LF Vandal Resistant Reader - black
<b>Supported ID Device Formats</b>	PAC, KeyPAC
<b>Supported Output Protocols</b>	PAC, Wiegand
<b>Audio / Visual Indicators</b>	Audible Sounder and Red/Green LEDs
<b>RFid Frequency</b>	Low Frequency (125kHz and 153.6kHz)
<b>Maximum Read Range</b>	40 mm / 1.57 in.
<b>Tamper Output</b>	Certified to EN 50131-1 and EN 50131-3
<b>Recommended Cabling</b>	PAC output 6-core 24 AWG alarm cable (unscreened) Wiegand output 5-core 22 AWG cable
<b>Power input(s)</b>	12–24V DC, <100mA @ 12V DC
<b>Dimensions</b>	100 (w) x 100 (h) x 16 (d) mm / 3.94 (w) x 3.94 (h) x 0.63 (d) in.
<b>Weight</b>	0.442 kg / 0.974 lb
<b>Material</b>	UL rated Polycarbonate
<b>Operating Temperature</b>	-40°C to +66°C / -40°F to 151°F
<b>Operating Humidity</b>	10% to 85% Relative Humidity
<b>Warranty</b>	Lifetime against electronic failure
<b>Standards Compliance</b>	UKCA, CE, UL, FCC, IC, RoHS & WEEE compliant
<b>Environment</b>	IP67 – Indoor / Outdoor weather resistant
<b>Intruder Grading</b>	Security Grade 3
<b>Country of Origin</b>	Italy