

## PAC 212

## Controllers

### 909033075 – PAC 212 LF - DIN mount

The PAC 212 Access controller range provides cost effective deployment of fully featured access control without the need for any additional software. Built on the PAC 512 controller, the PAC 212 is a standalone access controller that supports on-site programming via an on-board keypad.



Pre-wired with 3 Amp PSU in metal case with tamper switch and circuit

- In-built LF proximity reader
- Configurable for Residential or Commercial applications
- Up to 2,000 Keyholders
- Two Readers per channel when using PAC output readers
- Database and Events are exportable on USB drive (included) and viewable on any device with a Windows operating system

<b>Part Number(s)</b>	909033075 – PAC 212 LF - DIN mount
<b>Number of Doors Supported</b>	Two doors with up to four access control devices as per the following options: <ul style="list-style-type: none"> <li>• An access control reader per door</li> <li>• An access control reader and exit device (RTE) per door</li> <li>• Two access control readers per door (read-in and read-out)</li> </ul>
<b>Number of ID Devices Supported</b>	2,000
<b>Supported Credentials</b>	PAC (Cards and Tokens) Key PAC (Cards and Tokens)
<b>Event Storage</b>	4,000 events stored locally that can be exported to a PC via a USB memory device
<b>Configuration</b>	Locally using integrated keypad and administration reader or via PC with PAC software (4.6 version or above required)
<b>Additional Connections</b>	Tamper override
<b>LCD Display</b>	Backlit LCD display for full user notification and engineering settings
<b>Distance to Input Devices</b>	70m / 230ft
<b>Access Controller Input Devices</b>	PAC readers (LF, MT) PAC exit devices (RTE) Door contacts
<b>Input Connection Features</b>	Programmable relays for Door forced / left open 1 x tamper alarm input 1 x override input
<b>Output Connection Features</b>	2 x 5 Amp Lock relays @ 30V DC 2 x 5 Amp Auxiliary relays @ 30V DC

## PAC 212

## Controllers

<b>Output Formats</b>	PAC
<b>Recommended Cabling</b>	0.22mm 8-core alarm cable
<b>Power Input(s)</b>	12–24 V DC
<b>Dimensions</b>	181 (w) × 70 (h) × 125 (d) mm 7.13 (w) × 2.76 (h) × 4.92 (d) in
<b>Weight</b>	0.75 kg / 1.65 lb
<b>Operating Temperature</b>	0°C to +35°C / 32°F to 95°F°
<b>Operating Humidity</b>	10% to 85% Relative Humidity
<b>Warranty</b>	5 years against electronic failure
<b>Standards Compliance</b>	UKCA, CE, UL, FCC, IC, RoHS & WEEE compliant