



Compact or Mitred

Entrance Panels

GDX Entrance Panels

The GDX5 Entrance Panel is a high-quality door entry panel that has been designed and manufactured to withstand the harshest and most demanding of environments. The GDX5 Entrance Panel has an anti-vandal design which meets requirements for deploying in urban areas either at the entrance to properties or remote locations such as car park barriers or help points.

The Entrance Panel comes in two styles, Compact and Mitre Bezel:

- The mitre bezel panel is provided with a flush mounted backbox which fully surrounds the faceplate to offer very high protection from vandalism.
- The compact panel is available in flush mounted (standard) or surface mounted (option) and can also be provided with a surface mounted stainless-steel backbox.



Compact Panel yellow bezel example
Available as Flush and Surface mount



Mitre Panel example
Available as Flush mount only

<p>Product Number(s)</p> <p><i>Please refer to the Product Catalogue for full details of product options.</i></p>	<p><u>Compact Flush mount, functional</u> EPCO-001 to 015 1-15 buttons EPCO-001-Y to 015-Y 1-15 buttons yellow bezel</p> <p><u>Compact Flush mount, digital</u> EPCOD-001 to 006 12-15 buttons EPCOD-001-Y to 006-Y 12-15 buttons yellow bezel</p> <p><u>Compact Surface mount, functional</u> EPCOS-001 to 015 1-15 buttons EPCOS-001-Y to 015-Y 1-15 buttons yellow bezel</p> <p><u>Compact Surface mount, digital</u> EPCOSD-001 to 006 12-15 buttons EPCOSD-001-Y to 006-Y 12-15 buttons yellow bezel</p>	<p><u>Mitre Bezel, functional</u> EPMB-001 to 015 1-15 buttons EPMB-001-Y to 015-Y 1-15 buttons, yellow bezel</p> <p><u>Mitre Bezel, digital</u> EPMBD-001 to 006 12-15 buttons EPMBD-001-Y to 006-Y 12-15 buttons, yellow bezel</p>
<p>Audio Specification</p>	<p>Duplex</p>	
<p>Access Reader Options</p>	<p>Integrated: HF, LF External (using PAC Access Control): HF, LF No Access Reader</p>	
<p>Reader Supported Format</p>	<p>OPS™ format (High Frequency) PAC format (Low Frequency)</p>	



Compact or Mitred

Entrance Panels

LCD display	Backlit LCD display for full user notification and engineering settings	
Visual Indications	LCD displays message to confirm valid or invalid token presentation	
Audio Indications	Tone sounds for the release duration of the door Long Tone sounds for valid fob presentation Single bleep indicates invalid fob presentation	
Distance to Connected Inputs	Max. cable run 100 m	
Button Options	1 to 15 buttons that can be programmed to work functionally (dedicated button per residence) or digitally with a "CALL" button. Options for Equality Act compliant deployments include: <ul style="list-style-type: none">• Raster® Braille engraving• High Visibility yellow bezels	
Panel Engraving Options	Button labels <ul style="list-style-type: none">• Functional: numerical or alphabetical• Digital: Fixed labels for numbers 0–9 Address / location and colour logo options Service buttons have fixed labels (CALL, CANCEL, SERVICE, TRADE, CONCIERGE)	
Recommended Cabling	6-core 24 AWG alarm cable / CW1308 (unscreened) 1 x 2 core 1mm to Door Lock	
Power input	12V DC	
Power Requirements	0.35 Amp excluding locks	
Dimensions (mm / in.)	176 (w) × 303 (h) × 65 mm Note: Older Compact backboxes may be 55mm deep. Read installation manual for full mounting dimensions.	M155 (w) × 282 (h) × 75 (d) mm
Weight (kg / lb)	Approx. 2 kg	
Operating Temperature (°C / °F)	–10°C to +35°C	
Material	2.5mm high grade BS316 stainless-steel faceplate	
Warranty	5 years against electronic failure	
Standards Compliance	UKCA, CE, WEEE	
Environment	IP66	