

## GDX Audio & Video Handsets

These handsets provide 2-way audio and display a live colour video feed of the caller. This provides a more secure method to visually identify a caller before access is granted to a building or secure area.

- Available in 2-button (Enter & Privacy) and 3-button (Enter, Privacy & Concierge) models
- Raised and tactile 20mm buttons for DDA compliance
- Buttons LED-illuminated indicate the status of the handset
- 4" Colour TFT monitor
- Adjustable ring tone volume as standard



3-button handset

<b>Part Number(s)</b>	<b>HSVD-001</b> 2-button <b>HSVD-002</b> 3-button with concierge
<b>Button features</b>	<ul style="list-style-type: none"> <li>• <b>Concierge call</b> (3-button handset only)</li> <li>• <b>Privacy</b> (do not disturb)</li> <li>• <b>Enter</b> (unlock door to caller)</li> </ul>
<b>Release door lock</b>	Enter button releases door lock when call is active
<b>Do not disturb function</b>	Enabled by 'Privacy' button on handset
<b>DDA Options</b>	<ul style="list-style-type: none"> <li>• Each button has a raised tactile symbol and LED for indication</li> <li>• Hard of Hearing handset includes audio loop for use with hearing aids</li> </ul>
<b>Installer settings</b>	Adjustable ringer volume via pcb trimmer
<b>Distance to input devices</b>	Max. distance from Linecard 50 m Use separate 3-core cables for audio and video connections
<b>Power input(s)</b>	0.2 Amp @12V DC at standby (provided by the Linecard) 0.25 Amp when Video is in use
<b>Recommended cabling</b>	3 pair CW1308 or a minimum of CAT5e U/UTP twisted pair
<b>Dimensions (mm / in.)</b>	120 (w) x 313 (h) x 40 (d) mm
<b>Weight (kg / lb)</b>	0.6 kg / 1.32 lb
<b>Material</b>	ABS White
<b>Operating Temperature (°C / °F)</b>	0°C to +35°C
<b>Operating Humidity</b>	0% to 90% relative humidity
<b>Warranty</b>	5 years against electronic failure
<b>Standards &amp; Compliance</b>	CE, UKCA, WEEE