

Digital Entrance Panel Mitre

A robust entrance panel designed for flush mounting within the building environment, providing residents and visitors with a reliable and secure means of access to the property. Engineered for larger developments where the number of apartments exceeds 20.

Each panel includes buttons labelled 0–9, along with dedicated Call and Cancel buttons, and an optional Trade or Service button. As standard, the unit is equipped with a multi technology proximity reader capable of reading PAC OPS, legacy PAC, Indigo tokens, and a wide range of third party credentials.




Designed to operate seamlessly with the new GDX Next solution, the Entrance Panel provides clear duplex audio to residents' handsets. Each button sequence is programmed to call a specific property, with configuration carried out locally by the installation engineer. Integration with the GDX Next Central Control Unit (CCU) and Entrance Panel Expansion Unit (EEU) is intentionally simple, requiring only two cables: a standard CAT5e (U/UTP) and a 4-core RS-485 connection.

- **Equality** – Hard of hearing T-Coil compatible loop included
- **Access Control** – Integral multi-tech reader included
- **Visitor & Resident Feedback** – Dual line scrolling and static access and alarm messages
- **Simple Configuration** – Pre or locally configured button matrix saving installation time



Digital Mitre Entrance Panel with “CCT”, Call, Cancel, Trade and braille engraving

Product Family	Digital Entrance Panel Mitre <i>See reverse for all part numbers</i>
Audio Specification	Omnidirectional MEMS microphone providing outstanding sound clarity, even in challenging conditions
Access Reader Options	Integrated: Multi-Technology
Supported Reader Formats	PAC OPS, PAC OPS Lite, PAC, Indigo, various 3 rd -party HF and LF
Supported Output Formats	PAC Secure Data Bus
Max. Reading Range	30mm
Display	Dual line OLED screen with scrolling 1 and 2 lines
Visual Indication	Static and rolling information on means of calling a flat, access and alarm events
Audio Indication	Event specific sounds for flat calling, access and alarm events
Distance to CCU(A) or EEU(A)	100m for PAC Secure Data Bus (using 0.5mm ² 4-core cable) 100m for ethernet connection
Button Options	Up to 15 buttons

Panel Engraving Options	Address / location Colour logos Service buttons with fixed labels (SERVICE, TRADE)
Equality Act 2010 (UK) / Disability Discrimination Act (NI) compliance	Braille Yellow high visibility bezels Raised bump / pip on button 5 Optional verbal indication of door operations
Recommended Cabling	0.5mm ² 4-core unshielded cable for the Secure Data Bus connection Standard CAT6 (CAT5/5e/6 U/UTP) for ethernet
Tamper	Movement and cable
Power Input	400mA @ 40V provided by the CCU
Dimensions	Faceplate: 155 (w) × 282 (h) mm Flush backbox: 123 (w) × 255 (h) × 75 (d) mm
Weight	Approx 2.0 kg
Operating Temperature	-25°C to +55°C
Operating Humidity	RH max. 25 - 95% Environmental class A2
Material	Faceplate is made from 2.5mm high grade BW316 stainless steel
Warranty	5 years against electronic failure
Standards & Compliance	  
Environment	IPX4 IK08
Country of Origin	UK

Part numbers explained for ordering


Examples

FEPCS10YV

Functional Entrance Panel + Compact + Surface mount + 10 buttons + Yellow bezel + Video enabled

DEPMF14CCT

Digital Entrance Panel + Mitre + Flush mount + 14 buttons with "CC", "CCS" or "CCT" †



† "CC", "CCS", "CCT" refer to "Call", "Cancel", "Service" and "Trade" buttons